



MATERIAL SAFETY DATA SHEET

| | |
|--|---|
| Manufacturer: S.T.A.R., INC. 1400 Walcutt Road Columbus, Ohio 43228 | Emergency Phone No. CHEM-TEL 800-255-3924 Information Phone No. 614-870-0744 Effective Date 5/13/03 Supersedes Date |
|--|---|

SECTION I - IDENTIFICATION

Product Name: STAR ELASTO-BOND- PL ,HOT POUR CRACK FILLER
PARKING LOT SEALANT-

Chemical Family - Asphalt based crack filler.
Chemical Name - Proprietary
Prepared by - G.C. Dubey

H.M.I.S
 Health = 1
 Fire = 1
 Reactivity = 0

SECTION II – INGREDIENTS & HAZARDS

| Ingredients | WT% | Exposure Limits | | |
|---|-------|---|---------------------|-------------|
| | | OSHA | | |
| | | <u>PEL</u> | <u>TWA</u> | |
| PETROLEUM ASPHALT The dried film of this product may create dust when removed by sanding or grinding. | 50-55 | 15 mg/m3 (total) 5 mg/m3 (Respirable) | 5 mg/m3 | |
| | | ACGIH | | |
| | | <u>TLV</u> | <u>TWA</u> | |
| | | 5 mg/m3 (total) | 5mg/m3 (total) | |
| PETROLEUM OIL | 5-10 | <u>TWA</u> | <u>TLV</u> | <u>STEL</u> |
| | | 5 mg/m3 | 5 mg/m3 | 10 mg/m3 |
| | | (Mineral oil mist for all of above) | | |
| | | OSHA | | |
| | | <u>PEL</u> | <u>TWA</u> | |
| LIMESTONE | 20-25 | 15 mg/m3 (total) 5 mg/m3 (Respirable) | 5 mg/m3 10 mg/m3 | |
| | | ACGIH | | |
| | | <u>TLV</u> | <u>TWA</u> | |
| CARBON BLACK | 1-5 | 3.5 mg/m3 | 3.5 mg/m3 | |

SECTION III - PHYSICAL DATA

| <u>Boiling Point</u> | <u>Vapor Pressure</u> (mm Hg) | <u>Vapor Density</u> (Air=1) | <u>Appearance</u> |
|--|-----------------------------------|---------------------------------|-------------------------------------|
| Over 750 °F | approx. 25 | >1.0 | Black solid cube with asphalt odor. |
| <u>Evaporation Rate</u> (Water=1) | <u>Specific Gravity</u> by wt. | <u>% Volatile</u> | <u>Freezing Point</u> |
| <1 | 1.1 | 90-95 | Not applicable |
| <u>Miscibility With Water</u> Coefficient | <u>Threshold Odor</u> ppm | <u>pH</u> | <u>Water/Oil Distribution</u> |
| None | N/A | N/A | N/A |

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

| <u>Flammability Classification</u> | <u>Flash Point</u> (method used) | <u>Flammable Limits</u> | |
|------------------------------------|-------------------------------------|-------------------------|------------|
| HMIS Rating- 1 | 450 F /PMCC | LEL N/A | UEL N/A |

Extinguishing Media

Water fog, Foam, Dry Chemicals & CO2.

Unusual Fire and Explosion Hazards: None recognized.

Special Fire Fighting Procedures: Clear fire area of unprotected personnel. Do not enter confined area without helmet, face shield, bunker coat, gloves, rubber boots, and a self-contained breathing apparatus (SCUBA)

SECTION V- REACTIVITY DATA

| <u>Stability</u> | <u>Incompatibility (materials to avoid)</u> |
|------------------|---|
| Stable | Strong oxidizing agents and strong acids. |

Hazardous Polymerization- Will not occur.
Hazardous Decomposition Products- Oxides and compounds of Nitrogen and Sulfur, carbon monoxide, carbon dioxide, incomplete combustion products. Wear appropriate protective equipment

THE RECOMMENDATIONS AND INFORMATION PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AS THE DATE HEREOF. HOWEVER, SUCH INFORMATION AND RECOMMENDATIONS ARE PROVIDED WITHOUT WARRANTY OF ANY KIND AND S.T.A.R., INC. DISCLAIMS ANY AND ALL LIABILITY OR LEGAL RESPONSIBILITY FOR USE AND RELIANCE UPON THE SAME.