



PRODUCT BULLETIN

S.O.S. SEALER

(STAR OIL SPOT SEALER - LATEX BASED)

S.O.S Sealer grabs and seals the oil and grease spots on all types of asphaltic surfaces. The polymeric matrix and select surfactants in S.O.S. Sealer, result in a tough film that bonds aggressively to the oil spot, to offer a sound surface for the subsequent seal coating.

ADVANTAGES OF S.O.S. SEALER

- Dries quickly; in about 20 - 30 minutes
- Will stop oil from bleeding into the cured film of the seal coat
- Will not disbond from the oil spot and will not allow the sealer to peel away from primed areas
- Is water-based; ease in application, handling and clean-up
- Is supplied as a CONCENTRATE, thus offering benefits in warehousing, shipping, etc

SPECIFICATIONS AND DATA

Dilution Rate: One volume of S.O.S. Sealer with Two volumes of clean potable water. Coverage Rate:

Approximately 175 - 200 sq. yards per gallon of the S.O.S. Sealer concentrate. Method of Application: Brush, Roller or Spray.

Surface Preparation: Remove all loose dirt and scrape-off any heavy build-up of oil and grease. Hose off and let dry.

Apply the pre-diluted S.O.S. SEALER with a suitable applicator.

Do not apply, if rain is imminent within 8 hours or the ambient/surface temperature below 50 degrees F.

Precautions: Keep from freezing. KEEP OUT OF REACH OF CHILDREN.

Packaging: 5 gallon plastic pails and 55 gallon fiber drums.

Shipping Point: Columbus, Ohio and STAR plant locations throughout the continental U.S.A.

WARRANTY AND DISCLAIMER - These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. S.T.A.R. will not be responsible for any indirect or consequential damages. We will either replace or refund the purchase price in the event products are proven to be defective at our option.



1150 Milepost Drive
Columbus, Ohio 43228
(614) 870-0744 Fax 870-0598
800-759-1912